

Snelselectie COMFORT vloerverwarming

Hoofdverwarming

Draadstaalmatten (maasw: 150mm; draadd: 3mm; verzinkt)

Taanvoer water gem. = 40 °C; **Truimte = 20 °C**; Max 100m¹ tot 120m¹ buis per groep; **hoh = 150mm**; 6,7m¹ buis per m²

Te verwarmen oppervlak m ²			10	20	30	40	50	60	70	80	90	100
Afgifte (±110W/m ² (λ=0,0 keramisch)) kW			1,1	2,2	3,3	4,4	5,5	6,6	7,7	8,8	9,9	11
art. nrs												
CF Vloerverw.verd. A/R (aant gr)	groeps	496010.	1	2	2	3	3	4	5	5	6	7
Buis PE-RT 80m	per 1m	4950950	1	2	.	2	.	.	2	1	1	1
Buis PE-RT 120m	per 1m	4950955	.	.	2	1	3	4	3	4	5	6
Adapter 3/4 *16 Eurocon	stuks	3270200	2	4	4	6	6	8	10	10	12	14
Randisolatie 8mm	50 m ¹	4951200	1	1	1	1	2	2	2	3	3	3
CF Draadmat	2,52m ²	4960185	5	9	13	17	21	25	30	34	38	42
Binddraadjes CF (100 st)	per zak	4960170	2	2	5	6	8	10	11	12	13	16
Estrich emulsie (bus 10kg)	stuks	4951210	1	1	1	1	2	2	2	2	3	3

Bijverwarming

Draadstaalmatten (maasw: 150mm; draadd: 3mm; verzinkt)

Taanvoer water gem. = 40 °C; **Truimte = 20 °C**; Max 100m¹ tot 120m¹ buis per groep; **hoh = 300mm**; 3,4m¹ buis per m²

Te verwarmen oppervlak m ²			10	20	30	40	50	60	70	80	90	100
Afgifte (±75W/m ² (λ=0,0 keramisch)): kW			0,75	1,5	2,25	3	3,75	4,5	5,25	6	6,75	7,5
art. nrs												
CF Vloerverw.verd. A/R (aant gr)	groeps	496010.	1	1	1	2	2	2	3	3	3	4
Buis CF PEX-C 16*2 80mtr	per 1m	4950910	1	1	.	2	1	.	2	1	.	2
Buis CF PEX-C 16*2 120mtr	per 1m	4950915	.	.	1	.	1	2	1	2	3	2
Adapter 3/4 *16 Eurocon	stuks	3270200	2	2	2	4	4	4	6	6	6	8
Randisolatie 8mm	50 m ¹	4951200	1	1	1	1	2	2	2	3	3	3
CF Draadmat	2,52m ²	4960185	5	9	13	17	21	25	30	34	38	42
Binddraadjes CF (100 st)	per zak	4960170	2	2	3	4	4	5	6	7	8	8
Estrich emulsie (bus 10kg)	stuks	4951210	1	1	1	1	2	2	2	2	3	3